

Artex® Canvas is a strong, lightweight, extremely flexible white polyester fabric designed for upscale indoor printed signs and banners. Suitable for UV, solvent or screen-printing, it is tear and fade resistant, but is not suggested for outdoor use.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 6001	Polyester	Polyester
Yarn dtex	DIN EN ISO 2060	340 x 340	300 x 300
Type of Coating	N/A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	320 g/m ²	9.4 oz/yd ²
Tensile Strength	DIN EN ISO 1421	1.500/900 N/5 cm	171/102 lbs/inch
Flame Resistance	DIN 4102 B1	Flame Retardant	
Low Temperature (No Crack at:)			
Fungus Resistance	ASTM G21	Treated	
Puncture Resistance			
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Transit Shelter	Truckside
Applications		■						

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	□	■	■		

Available Sizes

Metric (m)	English (inches)
1.37, 1.60, 3.20, 5.00	54, 63, 126, 196

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)