

SuperSmooth™ Blockout is a 16 oz. smooth, scrimless, blockout banner material best suited for double sided signs and banners, compatible with UV, solvent or screen-printing. Engineered primarily for indoor use, SuperSmooth Blockout may be used outdoors for very short durations. With its low curl formula lay-flat appearance,, SuperSmooth Blockout is ideal for pop-up or scrolling banner stands, tradeshow and events graphics, POP and any hanging banner or sign. Widths range from 38" - 86.6".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN ISO 2076	Polyester	Polyester
Yard dtex	DIN EN ISO 2060	N/A	N/A
Type of Coating	N/A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	510 g/m ²	15 oz/yd ²
Tensile Strength	ASTM D 751 :2006, C.R.E	121 X 120 kgF	266 X 264 lbs/in
Tear Strength (warp/weft)	ASTM D 4830:1988 C.R.E	3.5 X 2.6 kgF	7.8 X 5.8 lbs/in
Low Temperature (No Crack at:)	ISO 1876	-20°C	-4°F
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes
Fungus Resistant	ASTM G21	Treated	

Applications

	Backlit	Banner	Billboard	Blockout	Building Wrap	Display Systems	Truckside
Applications		■		■		■	

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	□	■	■		

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.60, 2.20	38, 54, 63, 86

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)