

UltraCarpet™ Extra is a white tufted pile carpet especially made for solvent, eco-solvent and UV inkjet printing. Ink will not scratch off and drying time is minimal. It is best suited for indoor, digitally printed carpet or floor mats. UltraCarpet Extra is engineered for indoors use but can be used outdoors for short durations although it is ideal for use in corporate lobbies, waiting areas, foyers, tradeshow booths and ad floor graphics.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Pile	N/A	100% polyamide	100% polyamide
Construction	N/A	1/10" Top Tuft	1/10" Top Tuft
Total Height	N/A	5 mm	0.2"
Tuft Density	N/A	165900 /m ²	15412.5/sq.ft
Pile Weight	DIN EN ISO 2286-2	300 g/m ²	8.8 oz/yd ²
Total Weight	DIN EN ISO 2286-21	0.900 kg/m ² – 1.100	0.900 kg/m ² – 1.100
Primary Backing	ISO 13937-2-2002	AB and Latex	AB and Latex
Pile Height	DIN 53351	3 mm	0.12"
Fastness to Light	ISO 105 B01 (1 tm 8)	< 5	< 5
Fire Resistance	DIN 4102	Norm Bfl / s1	Norm Bfl / s1

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Carpet	Floor Mats	Truckside
Applications						■	■	

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	□	■	■		

Available Sizes

Metric (m)	English (inches)
1.80, 3.20, 5.00	71, 126, 196

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)