

UltraCanvas™ Artist C325 is 9.6 oz. and is woven from 100% polyester that is bath coated in Polyurethane then coated on one side with Acrylic. This feature allows for a unique dual print surface with one side having a gloss finish and the other a matte finish. This universal fabric can be used for a wide range of indoor and short-term outdoor applications. Available in widths ranging from 61" to 198".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	100% PES	100% Polyester
Type of Coating	N/A	Polyurethane bath coated with digital top coat on one side	
Total Weight	DIN EN ISO 2286-2	325 g/m ²	9.6 oz/yd ²
Breaking Force [N/5cm]	DIN EN ISO 13934-1	Warp – 2004	Weft – 2220
Elongation at tear [%]	DIN EN ISO 13934-1	Warp – 55.7	Weft – 35.5
Tear Resistance [N/25mm]	DIN EN ISO 9073-4	Warp – 307.6	Weft – 200.8
Flame Resistance	DIN 4102	NFPA701, B1	
Character	N/A	Heavy canvas texture with dual print surface	
Added Value	N/A	Print on digital side for a gloss finish and the Polyurethane side for a matte finish	
RF Weldable (Heat Sealable)		Testing in progress	

Note: All 198" (5.05m) textiles come on a 6" core only.

Applications

	Art Reprographic	Banners Indoor	Banners Outdoor	Displays	Flags	Theatrical	Tradeshow	Wall Covering
Applications	■	■	■	□		■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■		

Key: ■ - Excellent □ - Good

Available Sizes

Metric (m)	English (inches)
1.55, 2.50, 3.10, 5.05	61, 98, 122, 198

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)