

UltraCanvas™ Artist C325 is a woven 100% Polyester that is bath coated in Polyurethane then coated on one side with Acrylic. This feature allows for a unique dual print surface with one side having a gloss finish and the other a matte finish. This universal fabric can be used for a wide range of indoor and short-term outdoor applications.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 6001	100% PES	100% Polyester
Type of Coating	N/A	Polyurethane bath coated with Acrylic top coat on one side	
Total Weight	DIN EN ISO 2286-2	325 g/m ²	9.6 oz/yd ²
Breaking Force [N/5cm]	DIN EN ISO 13934-1	Warp – 2004	Weft – 2220
Elongation at tear [%]	DIN EN ISO 13934-1	Warp – 55.7	Weft – 35.5
Tear Resistance [N/25mm]	DIN EN ISO 9073-4	Warp – 307.6	Weft – 200.8
Flame Resistance	DIN 4102	NFPA701, B1	
Character	N/A	Heavy canvas texture with dual print surface	
Added Value	N/A	Print on Acrylic side for a gloss finish and the Polyurethane side for a matte finish	
RF Weldable (Heat Sealable)		Testing in progress	

Applications

	Art Reprographic	Banners Indoor	Banners Outdoor	Displays	Flags	Theatrical	Tradeshow	Wall Covering
Applications	■	■	■	□		■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■		

Available Sizes

Metric (m)	English (inches)
1.55, 2.50	61, 98

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)