

Ultravision - Window Perf

Description:

Ultravision™ is a perforated white PVC laminate graphic film (similar to standard pressure sensitive vinyl) with a black adhesive backside. Ultravision™ can be exterior mounted for short term (1 year) exciting window advertisement applications, as seen on store windows or busses. Your artwork can be printed on Ultravision™ by screen printing or digital printing. Ultravision™ is *not* for use with UV curable inks.

Physical Properties

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

CHARACTERISTICS	METRIC	ENGLISH
Vinyl Thickness	6.8	.008"
Release Sheet Thickness	6.7	.010"
Adhesive Thickness	.9-1.0	.015"
Minimum Application Temperature	+4°C	+40°F
Open Area	50% (Approximately)	
Service Temperature Range	-4° to +39°C	20°F to +100°F
Storage Stability	21°C	70°F
Size	.965m, 1.35m	38", 53"
Water Resistance	Not recommended where immersed	
Humidity Resistance	Fair	
Solvent Resistance	Good	
Dimensional Stability	Good	
Color Available	White with black adhesive backing	
Printing	Standard vinyl inks recommended. Print image on non-adhesive side of product, not adhesive side	
Application	Apply to dry, clean glass surface	

