

# TECHNICAL DATA SHEET

## UltraProgress Carpet

### DESCRIPTION:

UltraProgress Carpet is a non woven printable carpet suitable for solvent, UV and dye-sublimation printers. It is best suited for indoor carpet or door mats. UltraProgress Carpet is engineered for indoor use but can be used outdoors for short durations and is ideal for use in corporate lobbies, waiting areas, foyers and trade show booth floor graphics.

### PHYSICAL PROPERTIES:

*The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guaranty and do not constitute a warranty. Therefore, the results obtained from the use thereof, or that any use will not infringe upon any patent. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)*

Characteristics	Test Method	Metric	English
Pile	N/A	100% polyester	100% polyester
Construction	N/A	Non woven with pre-coat	Non woven with pre-coat
Total Height	N/A	1.8 mm	0.07" inch
Tuft Density	N/A	n/a	n/a
Pile Weight	TPA 1 ISO 9073 T.2	250 g/m <sup>2</sup>	8 oz/yd <sup>2</sup>
Total Weight	TPA 1 ISO 9073 T.1	750 g/m <sup>2</sup>	24 oz/yd <sup>2</sup>
Primary Backing	ISO 13937-2-2001	Latex	Latex
Pile Height	DIN 53351	3 mm	0.12" inch
Width	TPA 1 ISO 9073 T.8	1.6M & 3.2M	63" & 126"
Roll length	In production	25	82 Ft.
Fastness to Light	ISO 105 B01 (1 tm 8)	< 5	< 5
Fire Resistance	DIN 4102	norm Bfl / S1	norm Bfl / S1

ULTRAFLEX SYSTEMS, INC.  
1578 Sussex Tpke, Bldg 4; Randolph, NJ 07869 USA  
TEL. 973-627-8608\*FAX. 973-627-8506\* EMAIL: [SALES@ULTRAFLEXX.COM](mailto:SALES@ULTRAFLEXX.COM)  
[WWW.ULTRAFLEXX.COM](http://WWW.ULTRAFLEXX.COM)

7/2008