

SuperPrint® Pro FL is a 12 oz. gloss finish, economical, light-weight, front-lit banner material. Tear and fade resistant and is ideal for banners, signs and billboards. Works with UV, solvent or screen-printing and is available in a 196" width.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	Polyester	Polyester
Yarn dtex	DIN EN ISO 2060	924 x 924 dtex	840 x 840 denier
Type of Coating	N/A	PVC	PVC
Total Weight	DIN EN ISO 2286-2	400 g/m ²	12 oz/yd ²
Tensile Strength	DIN 13934-1999	132 x 117 (kg/5cm)	148 x 131 (lb/in)
Tear Strength (warp/weft)	ISO 13937-2-2000	21 x 18 kg	46 x 39 lb
Flame Resistance	DIN 4102	NFPA701, NYC (MEA)	
Low Temperature (No Crack at:)	ASTM D 2137	-20°C	-4°F
RF Weldable (Heat Sealable)	DIN 53354	Yes	Yes
Fungus Resistant	ASTM G21	Treated	

Applications

	Backlit	Banner	Billboard	Blockout	Building Wrap	Display Systems	Truckside
Applications		■	■			■	

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	□	■	■		

Available Sizes

Metric (m)	English (inches)
5.00	196

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)