

UltraCanvas PES C380 is 11.2 oz. and is made of a woven micro-fiber that is 100% polyester with a digital coating on one side. This opaque heavy canvas lays flat, has no curling and does not fray; allowing for easy finishing. It can be used for in indoor and short-term outdoor applications. Available in widths ranging from 61” to 198”.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 6001	100% PES	100% Polyester
Type of Coating	N/A	Digital coating on one side	
Total Weight	DIN EN ISO 2286-2	380 g/m ²	11.2 oz/yd ²
Breaking Force [N/5cm]	DIN EN ISO 13934-1	Warp – 4432 Weft – 1061	
Elongation at tear [%]	DIN EN ISO 13934-1	Warp – 34.8 Weft – 16.3	
Tear Resistance [N/25mm]	DIN EN ISO 9073-4	Warp – 563 Weft – 107	
Flame Resistance	DIN 4102	NFPA701, California FR, B1	
Character	N/A	Heavy canvas texture	
Added Value	N/A	Opaque, lays flat and does not curl	
RF Weldable (Heat Sealable)		Testing in progress	

Applications

	Art Reprographic	Banners Indoor	Banners Outdoor	Displays	Flags	Theatrical	Tradeshow	Wall Covering
Applications	■	■	■	□		■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■		

Available Sizes

Metric (m)	English (inches)
1.55, 3.10, 5.05	61, 122, 198

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)