

Outdoor Blockout LTX is a heavy duty banner material used for indoor and outdoor applications. The unique construction provides strength and stability under harsh weather conditions. Outdoor Blockout LTX is an 18 oz. material designed for two-sided applications. The material is one of the few blockouts on the market that may be printed double-sided on Latex devices. Both sides of the material have a matte finish and are compatible for use with solvent, eco-solvent, UV, Latex and screen printing. Available in widths from 38+ to 196+.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Type of Coating	N/A	PVC	PVC
Total Weight		610gsm	18oz/yd ²
Tensile Strength	ISO 13934-1:1999	2400 x 2000 N/5cm	302.36 x 228.40 lbs/in
Tear Strength (warp/weft)	DIN 53356 BS3424	140 x 140 N	31.47 x 31.47 lbs/in
Flame Resistance	NFPA701, Title 19, CSFM		
Low Temperature (No Crack at:)	DIN 53351	Low at -20°C	Low at -4°F
RF Weldable (Heat Sealable)	YES		
Fungus Resistant	YES		

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications		■	■	■		■	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	* ■	■		

*Certified for HP Latex Inks

Available Sizes

Metric (m)	English (inches)
0.965, 1.37, 1.52, 1.60, 2.03, 2.64, 3.20, 5.00	38+, 54+, 60+, 63+, 80+, 104+, 126+, 196+

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)