

FabriTac® is a removable, adhesive fabric that may be mounted to any surface and repositioned countless times. FabriTac will retain its adhesion and leaves no residue. FabriTac has a unique coating which is quick drying and water resistant. The material provides superb quality, color gamut and resolution and is compatible for use with solvent, eco-solvent, UV and Latex inks. FabriTac is designed with unique opaque properties which prevents translucency problems associated with comparable products. Available in widths from 42" - 60".

Material Details

| CHARACTERISTICS | TEST METHOD | METRIC | ENGLISH |
|-------------------------|---|---------------------|-------------------------|
| Support Cloth | DIN 60001 | Polyester | Polyester |
| Yarn dtex | DIN EN ISO 2060 | 166 x 166 dtex | 150 x 150 denier |
| Adhesive | White Repositionable Adhesive | | |
| Total Weight | ISO 534 | 350g/m ² | 10.3 oz/yd ² |
| Release Film | Paper Liner 100g (Both sides PE) | | |
| Flame Resistance | ASTME 84 Class A, NFPA 286 | | |
| Storage Recommendations | <ul style="list-style-type: none"> •All Ultraflex materials should be stored in their original packaging. •FabriTac should be stored in temperatures between 10° and 20° Celsius, and a relative humidity of 20% - 60%. | | |

Applications

| | Outdoor Advertising | Banner | Floor Decals | Posters | Stickers | Wall Graphics | POP/POS |
|--------------|---------------------|--------|--------------|---------|----------|---------------|---------|
| Applications | ■ | ■ | ■ | ■ | ■ | ■ | ■ |

Ink Printability

| Solvent | Eco Solvent | UV | Latex | Screen Printing | Dye Transfer | Dye Direct |
|---------|-------------|----|-------|-----------------|--------------|------------|
| ■ | ■ | ■ | * ■ | | | |

Available Sizes

| Metric (m) | English (inches) |
|-------------------|------------------|
| 1.067, 1.37, 1.52 | 42, 54 ,60 |

*Certified for HP Latex Inks

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)