

UltraCanvas® Light S190 is a 5.9 oz., 100% polyester woven material that has been bath-coated with our Universal coating. The light canvas construction makes it ideal for back-lit or front-lit graphics used for indoor and short-term out door applications. The material provides good bleed through making it ideal for two-way graphics. UltraCanvas Light S190 has water repellent properties making it a great material for short-term event structures and pop-up tents. Available in widths of 122" and 198".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN ISO 2286-2	100% Polyester	100% Polyester
Type of Coating	N/A	Single side coated	
Total Weight	DIN EN ISO 2286-2	190 g/m ²	5.9 oz/yd ²
Breaking Force [N/5cm]	DIN EN ISO 13934-1	Testing in progress	
Elongation at tear [%]	DIN EN ISO 13934-1	Testing in progress	
Tear Resistance [N/25mm]	DIN EN ISO 9073-4	Testing in progress	
Flame Resistance	DIN 4102	NFPA701, B1, ASTM E84	
Character	N/A	Light canvas texture	
Added Value	N/A	Can be back-lit and front-lit	
RF Weldable (Heat Sealable)		Testing in progress	

Applications

	Art Reprographic	Banners Indoor	Banners Outdoor	Displays	Flags	Theatrical	Tradeshow	Wall Covering
Applications	■	■	■	■		■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■	■	■

Available Sizes

Metric (m)	English (inches)
3.10, 5.05	122, 198

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)