

# Technical Data Sheet

## SuperSmooth<sup>™</sup> PET GreyBack

SuperSmooth™ PET GreyBack is a 13 oz. non-curling banner with a super smooth print surface and a grey back. The material is ideal for high resolution printing. The grey back-side prevents light transparency and shadowing. SuperSmooth PET GreyBack is ideal for pop-up, roll-up, x-displays and an array of close viewing indoor applications. The material does not require lamination and is available in a matte finish.SuperSmooth PET Greyback is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. Available in widths from 38" - 126".

#### **Material Details**

CHARACTERISTICS	TEST METHOD METRIC		ENGLISH	
Support Cloth	DIN ISO 2076	Polyethylene terephthalate		
Yard dtex	DIN EN ISO 2060	N/A	N/A	
Total Weight	DIN EN ISO 2286-2	450 g/m <sup>2</sup>	13 oz/yd <sup>2</sup>	
Tensile Strength	GB/T10403-2006	1288 x 1492 N/5cm	147.08 x 170.38lbs/inch	
Tear Strength (warp/weft)	HG/T2581-1994	3.6 x 3.5 N/5cm	0.41 x0.39 lbs/inch	

#### **Applications**

	Pop-Up Displays	Banner	Roll-Up Displays	Blockout	Scrolling Signs	X-Displays	Trade Show Displays
Applications							

### Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct

#### **Available Sizes**

Metric (m)	English (inches)
0.965, 1.37, 1.60,	38", 54", 63",
2.03, 3.20	80", 126"

HP Latex Certified\*

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

**ULTRAFLEX** 

www.ultrafleXX.com updated: 06/2019

> Ultraflex Systems Inc. Headquarters 6333 Pelican Creek Circle, Riverview, FL 33578 P: (973)627-8608 Email: sales@Ultraflexx.com

Ultraflex Systems Inc. 1578 Sussex Turnpike, Bldg. 4 Randolph, NJ 07869 P: (973)627-8608 F: (973)627-8506 Email: sales@ultraflexx.com Ultraflex Europe Unit 15 Eltisley Business Park Abbotsley, Cambridgeshire UK PE19 6TX Phone: (44)1767-677-100

Email: sales@ultraflexeurope.com