

## **Technical Data Sheet**

# UltraMesh® Premium 328

UltraMesh® Premium 328 is a 10 oz. coated, polyester mesh banner substrate that is engineered for building wraps, fence graphics, barricade graphics and a variety of indoor and outdoor applications. UltraMesh Premium 328 allows 30% air-flow through and is REACH compliant. The material has a premium white coating which provides vivid graphic production and consistent color management from batch to batch. UltraMesh Premium 328 is compatible for use with solvent, eco-solvent, UV, Latex and screen printing. The material is the choice for print professional seeking to improve efficiency and reduce seam frequency in grand format applications. Available in widths of 126" and 196".

### **Material Details**

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH	
Support Cloth	DIN ISO 2076	DIN ISO 2076 Polye		
Yard dtex	DIN EN ISO 2060	1100 x 1100 dtex	1000 x 1000 denier	
Coating Type		Р	VC	
Total Weight	DIN EN ISO 2286-2	340 g/m <sup>2</sup>	10 oz/yd <sup>2</sup>	
Tensile Strength	DIN EN ISO 1421	2400 x 1500 N/5cm	273 x 171 lbs/in	
Tear Strength (warp/weft)	DIN 53363	300 x 250 N	67 x 56 lbs	
Air Permeability	DIN EN ISO 9237	1400 l/m²/s		
RF Weldable (Heat Sealable)	F Weldable (Heat Sealable) DIN 53354		Yes	
Percentage of Opening	30%			
Fire Resistance	NFPA701, Title 19, CSFM			

### **Applications**

	Building	Fence	Stadium	Barricade	Street	Indoor	Outdoor
	Wraps	Graphics	Graphics	Graphics	Graphics	Graphics	Graphics
Applications							

## Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
			*■			

#### Available Sizes

Metric (m)	English (inches)		
3.20m x 100m	126" x 328'		
5.00m x 100m	196" x 328'		

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



www.ultrafleXX.com updated: 06/2019

Ultraflex Systems Inc.
Headquarters
6333 Pelican Creek Circle,
Riverview, FL 33578
P: (973)627-8608
Email: sales@Ultraflexx.com

Ultraflex Systems Inc. 1578 Sussex Turnpike, Bldg. 4 Randolph, NJ 07869 P: (973)627-8608 F: (973)627-8506 Email: sales@ultraflexx.com

Ultraflex Europe Unit 15 Eltisley Business Park Abbotsley, Cambridgeshire UK PE19 6TX Phone: (44)1767-677-100

Email: sales@ultraflexeurope.com

<sup>\*</sup>Certified for HP Latex Inks