

Bravura™ Display 450 is a 450 micron, non-curl, PP and PET film designed specifically for pop-up display systems. The material has a smooth print surface and a quick drying top coat and bright white point. Bravura Display 450 has a white backside that prevents translucency issues. Bravura Display 450 is solvent, eco-solvent, UV & Latex printable. Available in widths from 36" – 60" on 98' long rolls.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Base Material		PP & PET	
Total Weight	ASTM D646	520±5 g/m <sup>2</sup>	15.33oz/yd <sup>2</sup>
Total Thickness	ASTM D645	450 micron	
Whiteness	ASTM E313	95	
Opacity	ISO 2471	> 99.99	
Surface Finish		Semi-Matte	

### Applications

	Back-lit Banners	Blockout	Exhibition Panels	Special Effects Displays	Transit Graphics	Display Systems	High Res. Posters
Applications		■	■	■	■	■	■

### Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■*			

### Available Sizes

Metric (m)	English (inches)
0.914, 1.37, 1.52	36", 54", 60"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)