

Technical Data Sheet

ReSource™ Eclipse® D260

ReSource Eclipse® D260 is an 8 oz., 100% polyester, soft blockout material with a black back. The material is crease-free for easy folding and shipping, dimensionally stable and opaque. ReSource Eclipse is ideal for pop-ups, framing systems, tradeshow graphics and other display applications. ReSource Eclipse® D260 is printable via UV and Latex. Available in widths ranging from 63" to 196".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH	
Base Fabric		100% Polyester		
Total Weight	DIN EN ISO 2286-2	260 g/m²	8 oz/yd²	
Fire Resistance	DIN EN 13501-1			
Thickness		0.30 mm	16 mil	
Tensile strength	DIN EN ISO 1421-1	1600 x 1000 N/ 5cm	182.72 x 114.2 lbs/ inch	
Tear Strength	DIN 53363	250 x 200 N	56.2 x 44.9 lbf	

Applications

	Banner Stands	Banners Indoor	Projection	Light Box	Display Systems	Theater	Exhibition	Wall Advertising
Application								

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct

Available Sizes

Metric (m)	English (inches)		
1.60, 3.2, 5.0	63, 126, 196		

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

ULTRAFLEX

www.ultrafleXX.com updated: 03/2020

> Ultraflex Systems Inc. Headquarters 6333 Pelican Creek Circle, Riverview, FL 33578 P: (973)627-8608

Ultraflex Systems Inc. 1578 Sussex Turnpike, Bldg. 4 Randolph, NJ 07869 P: (973)627-8608 F: (973)627-8506

Ultraflex Europe Unit 15 Eltisley Business Park Abbotsley, Cambridgeshire UK PE19 6TX

Phone: (44)1767-677-100 Email: sales@ultraflexeurope.com