

100% PVC-free / phthalate-free, durable substrate ideal for a wide range of indoor applications including banners, banner stands, and POS. This material has a double-sided print surface and complete opacity to prevent translucency and shadowing. EcoVantage DSS Blockout is compatible with solvent, eco-solvent, UV, Latex and screen printing and available in widths up to 126”.

Material Details

CHARACTERISTICS		METRIC	ENGLISH
Composition	DIN 60001, ASTM D7641	100% Polyester	
Total Weight	DIN EN ISO 2286-2 ASTM D751	300 g/m ²	8.85 oz./yd ²
Denier	DIN EN ISO 2060, ASTM D 1907	300 x 300	
Tensile Strength	DIN EN ISO 1421	1205 x 1100 N/5cm	137.61 x 125.6 lbs/in
Tear Strength	DIN 53363	80 x 68 N	18 x 15.29 lbs
Fire Resistance	NFPA 701		

Applications

	POP	Banner	Banner Stands	Block-out	Tradeshow Graphics	Display Systems	Indoor Banners
Applications	■	■	■	■	■	■	■

Ink Printability

Available Sizes

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

Metric (m)	English (inches)
1.37, 1.60, 3.20	54", 63", 126"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)