

100% PVC-free / phthalate-free, mesh substrate ideal for a wide range of indoor / outdoor applications including building wraps, fences, barricades, and stadium graphics. This lightweight material also has a non-PVC coated surface. UltraMesh EcoVantage is compatible with solvent, eco-solvent, UV, Latex and screen printing and available in 126" width.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Composition	DIN 60001, ASTM D7641	100% Polyester	
Total Weight	DIN EN ISO 2286-2 ASTM D751	190 g/m <sup>2</sup>	5.6 oz./yd <sup>2</sup>
Denier	DIN EN ISO 2060, ASTM D 1907	1000 x 1000	
Tensile Strength	DIN EN ISO 1421	1500 x 1550 N/5cm	171.3 x 177.01 lbs/in
Tear Strength	DIN 53363	450 x 310 N	101 x 69 lbs
Welding	Weldable with aide		
Fire Resistance	NFPA 701		

### Applications

	Building Wraps	Fence Graphics	Stadium Graphics	Barricade Graphics	Street Graphics	Indoor Graphics	Outdoor Graphics
Applications	■	■	■	■	■	■	■

### Ink Printability

### Available Sizes

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

Metric (m)	English (inches)
3.20	126"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)