

VorTex™ Transfer Paper XA 65gsm is a versatile dye sublimation transfer paper engineered for all polyester materials. The material is ideal for many applications such as banners, flags and personalized interior. The VorTex Transfer Paper XA 65gsm has an excellent transfer yield with very high ink release and efficiency. The material allows for superfine detailed printing has great dimensional stability, fast drying time and easy handling. VorTex Transfer Paper XA 65gsm is available in widths of 63" & 126" on 150m length rolls.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Weight	ISO 536	65 gsm	1.95 oz/yd <sup>2</sup>
Caliper	ISO 534	86 µm	3.38 mil
Sizing Cobb	ISO 535	28 gsm	0.83 oz/yd <sup>2</sup>
Recommended Temperature Settings	N/A	195 – 205° C	383 – 401 °F
Recommended Time Settings	N/A	35 – 55"	
Heat Setting Temperature	N/A	200 – 230 °C	
Handling & Storage	Conditions with a relative humidity 40-50% and room temperature of 68 – 78.8 °F		

### Applications

	Banner	Flags	Interior
Applications	■	■	■

### Available Sizes

Metric (m)	English (inches)
1.60, 3.20	63", 126"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)