

100% PVC-free / phthalate-free, heavy-duty substrate with a scrim fabric that provides additional strength and stability under harsh weather conditions. This material has a coated, double-sided print surface and complete opacity to prevent translucency and shadowing. EcoVantage Pole Banner is compatible with solvent, eco-solvent, UV, Latex and screen printing and available in widths from 54" to 126".

Material Details

CHARACTERISTICS	TEST	METRIC	ENGLISH
Composition	DIN 60001, D7641	100% Polyester	
Total Weight	DIN EN ISO 2286-2 ASTM D751	380 g/m ²	11.2 oz/yd ²
Denier	DIN EN ISO 2060, ASTM D 1907	1000 x 1000	
Tensile Strength	DIN EN ISO 1421	2800 x 1600 N/5cm	320 x 183 lbs/in
Tear Strength	DIN 53363	440 x 390 N	99 x 88 lbs
Fire Resistance	NFPA 701		

Applications

	Display System	Banner	Truckside	Blockout	Scrolling Signs	Outdoor	Trade Show Displays
Applications	■	■	■	■		■	■

Ink Printability

Available Sizes

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■		

Metric (m)	English (inches)
1.37, 1.60, 3.20	54", 63", 126"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)