

UltraCarpet® Pantone is a white, tufted-pile carpet made specially for dye sublimation printing. The ink will not scratch off and drying time is minimal. UltraCarpet Pantone has been engineered for indoor, digitally printed carpet or doormats. The material may be used outdoors for short periods of time. UltraCarpet Pantone is ideal for corporate lobbies, waiting areas, foyers, tradeshow booths, retail stores and floor graphics. Available in widths of 126" and 158".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Pile	N/A	100% polyamide 6	100% polyamide 6
Construction	N/A	Tuft special layer	Tuft special layer
Total Height	N/A	4 mm	0.157"
Tuft Density	N/A	165900 /m ²	15412.5/sq.ft
Pile Weight	DIN EN ISO 2286-2	500 g/m ²	14.75 oz/yd ²
Total Weight	DIN EN ISO 2286-21	1.200 kg/m ²	35.39 oz/yd ²
Primary Backing	ISO 13937-2-2002	AB and Latex	AB and Latex
Pile Height	DIN 53351	3 mm	0.12"
Fastness to Light	ISO 105 B01 (1 tm 8)	< 5	
Fire Resistance	DIN 4102	Norm Cfl /s1	

Applications

	Back-lit	Banner	Billboard	Blockout	Building Wrap	Carpet	Floor Mats	Truckside
Applications						■	■	

Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
		■	■		■	■

Available Sizes

Metric (m)	English (inches)
3.2, 4	126", 158"

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)