

Received: 08/17/2015	Completed: 08/18/2015	Letter: H1	BG	P.O.#:	Test Report #:	3-09355-1-
Client's Identification	Style: Vortex Backlit Precision T130 . Composition: Polyester. Product End Use: Banners/Signs.					
Tested For: Kylie Schleicher Ultraflex Systems Inc. 1578 Sussex Tpk., Bldg. #4 Randolph, NJ 07869				Key Test: CA 1237 Sm		175
				Tel: 1-(973)-627-8608		Ext:
				Fax: 1-()- -		

PC: 1H /jd SM/mg

TEST PERFORMED: **California Fire Marshal Title 19: Section 1237** (Proposed Revision 8/9/93) Fire Resistance; Small Scale Test - INTERIOR MATERIALS QUALIFICATION

RESULTS REPORTED: ☒ Initially
☐ After 3 dry cleanings
☐ After 5 launderings @ 160°F

RESULTS:	Specimen #	Afterflame (seconds)	Afterglow (seconds)	Char Length (inches)
	-----	-----	-----	-----
Warp:	1	0	0	3.5
	2	0	0	3.9
	3	0	0	4.1
	4	0	0	4.2
	5	0	0	5.0

	Avg:	0		
Fill:	6	0	0	4.1
	7	0	0	4.9
	8	0	0	5.1
	9	0	0	4.2
	10	0	0	4.3

	Avg:	0		

APPROXIMATE WEIGHT OF MATERIAL (as measured by Govmark): 4.3 oz/yd²

ACCEPTANCE CRITERIA:

Afterflame: 4.0 seconds maximum average for warp or fill
Afterglow: (see Note #2 below)
Char Length: 6.0 inches maximum for any individual specimen

NOTES:

1. An asterisk (*) next to any char length measurement indicates that a part of the char length is melt away due to heat from the flame source and not from propagating flame. Therefore, the sample submitted meets the requirements of Title 19 - California Code of Regulations, Section 1237 and 1237.1 for materials weighing less than 4 oz/yd².
2. Afterglow is required to be reported; however, it is not factored into the Acceptance Criteria.

Received:08/17/2015	Completed:08/18/2015	Letter: H1	BG	P.O.#:	Test Report #:	3-09355-1-
Client's Identification	Style: Vortex Backlit Precision T130. Composition: Polyester. Product End Use: Banners/Signs.					
Tested For: Kylie Schleicher Ultraflex Systems Inc. 1578 Sussex Tpk., Bldg. #4 Randolph, NJ 07869				Key Test: CA 1237 Sm		175
				Tel: 1-(973)-627-8608		Ext:
				Fax: 1-()- -		

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

☒ Complies; ☐ Does not comply

REMARKS: None.

NOTE: The number of test specimens and Acceptance Criteria are based on a proposed revision issued and implemented by the California State Fire Marshal in August 1993. In substance, the following has occurred:


1. A maximum afterflame of 4 seconds is permitted as opposed to 1 second.
2. It was clarified that the char length maximum of 6 inches applies to any individual specimen and is not an average requirement.
3. Ten specimens are tested in lieu of 6 specimens.

This report issues the conclusion to Section 1237 based on the California State Fire Marshal's continued endorsement of the proposed revision.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by California Fire Marshal Title 19: Section 1237 Small Scale (Proposed Revision 8/9/93).

MS. PHYLLIS PETTIT

AUG 20 2015



AUTHORIZED SIGNATURE
GOVMARK
/ec 

(Page 2 of 2)