



GOVMARK

96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
email: govmark.accounting@sgs.com

Page 1

Received: 09/10/2019 Completed: 09/10/2019 Letter: M BG P.O.#: Test Report #: 3-34425-0-

Client's Identification

Style: Vortex Triple White D251. Product End Use: Banners/Signage.

Tested For: Kylie Schleicher**Key Test: CA 1237 Sm**

250

Ultraflex Systems Inc.

1578 Sussex Tpk., Bldg. #4

Randolph, NJ 07869

Tel: 1-(973)-627-8608**Ext:****Fax: 1-()- -**

LE: 1993; V 02/19

PC: 1H /jd SM/mg

TEST PERFORMED: California Fire Marshal Title 19: Section 1237 (Proposed Revision 8/9/93) Fire Resistance; Small Scale Test - INTERIOR MATERIALS QUALIFICATION

RESULTS REPORTED: [x] Initially
[] After 3 dry cleanings
[] After 5 launderings @ 160°F

RESULTS:

	Specimen #	Afterflame (seconds)	Afterglow (seconds)	Char Length (inches)
Warp:	1	0.0	0	4.9
	2	0.0	0	4.6
	3	0.0	0	4.8
	4	2.7	0	5.1
	5	3.9	0	4.9
	Avg:	1.3		
Fill:	6	0.0	0	4.8
	7	0.0	0	4.7
	8	0.0	0	4.7
	9	4.8	0	5.2
	10	5.4	0	4.4
	Avg:	2.0		

APPROXIMATE WEIGHT OF MATERIAL (as measured by SGS Govmark): 7.3 oz/yd²**ACCEPTANCE CRITERIA:**

Afterflame: 4.0 seconds maximum average for warp or fill
Afterglow: (see Note #2 below)
Char Length: 6.0 inches maximum for any individual specimen

NOTES:

1. An asterisk (*) next to any char length measurement indicates that a part of the char length is melt away due to heat from the flame source and not from propagating flame. Therefore, the sample submitted meets the requirements of Title 19 - California Code of Regulations, Section 1237 and 1237.1 for materials weighing less than 4 oz/yd².

2. Afterglow is required to be reported; however, it is not factored into the Acceptance Criteria.

(Page 1 of 2)



GOVMARK

96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
email: govmark.accounting@sgs.com

Page 2

Received:09/10/2019	Completed:09/10/2019	Letter: M	BG	P.O.#:	Test Report #:	3-34425-0-
Client's Identification	Style: Vortex Triple White D251. Product End Use: Banners/Signage.					
Tested For: Kylie Schleicher Ultraflex Systems Inc. 1578 Sussex Tpk., Bldg. #4 Randolph, NJ 07869				Key Test: CA 1237 Sm		250
				Tel: 1-(973)-627-8608		Ext:
				Fax: 1-()- -		

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:

☒ [x] Complies; ☐ [] Does not comply


REMARKS: None.

NOTE: The number of test specimens and Acceptance Criteria are based on a proposed revision issued and implemented by the California State Fire Marshal in August 1993. In substance, the following has occurred:

1. A maximum afterflame of 4 seconds is permitted as opposed to 1 second.
2. It was clarified that the char length maximum of 6 inches applies to any individual specimen and is not an average requirement.
3. Ten specimens are tested in lieu of 6 specimens.

This report issues the conclusion to Section 1237 based on the California State Fire Marshal's continued endorsement of the proposed revision.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

 **Jillian Guillem**

AUTHORIZED SIGNATURE

SGS GOVMARK

SEP 12 2019

/ab /pm

(Page 2 of 2)